

HMT120温度变送器

Vaisala温度变送器		HMT120											价格	
1 输出参数	温度	T												
2 变送器类型	墙面安装式/固定探头	A												
	远程探头, 带3米电缆	B												
	远程探头, 带5米电缆	C												
	远程探头, 带10米电缆	D												
	远程探头, 带10米电缆+10米延长	E												
	远程探头, 带20米电缆	F												
3 显示	无显示	0												
	有显示	1												
4 信号输出	4...20 mA		两线制回路供电	A										
5 通道1输出参数	温度	-40...+60 °C	(-40...+140 °F)		B									
		-20...+80 °C	(-4...+176 °F)		C									
		0...+60 °C	(+32...+140 °F)		D									
		-40...+80 °C	(-40...+176 °F)		E									
	特殊	参数	T	量程	X									
6 通道2输出参数	无				A									
7 显示单位	公制									1				
	非公制									2				
8 传感器保护	塑料格栅										1			
	塑料格栅, 带PTFE过滤器										2			
	不锈钢烧结过滤器 (只适用于远程探头)										3			
	特氟龙烧结过滤器										E			
9 变送器安装件	无										A			
	带防雨罩的安装背板 (215109)										C			
10 探头安装组件	无											1		
	管道安装件 (215619)											2		
	探头安装法兰 (226061)											3		
	室外安装: DTR504A 防辐射罩 (DTR504A)											5		
	探头安装夹, 1个 (225501)											6		
11 电缆套件	密封式电缆套(gland), 适用2...6 mm直径电缆												A	
	管道式电缆套 PG9												B	
	管道式电缆套 NPT 1/2"												C	
	无电缆套 (橡胶塞)												D	
	上述各种套件 (包含A, B, C and D)												Z	
12 与PC机连接附件	无											0		
	与PC机连接的服务电缆, USB接口 (219685)											1		
13 操作手册	无												A	
	多语种手册												Z	

单价
数量
总价

粗体字的选型已包括在基本价格中, 斜体字的选项要附加价格
此选型表由英文版本翻译而得, 如有不妥之处, 敬请参照英文选型表

典型选型

HMT120	T	A	0	A	B	A	1	1	A	1	A	0	Z
--------	---	---	---	---	---	---	---	---	---	---	---	---	---